



**NEW! Thermo Scientific Revco PLUS
Ultra-Low Temperature Upright Freezers**

Maximizing Critical Sample Protection and Storage

Innovative Features and Rewarding Benefits

Features	Advantage	Benefit	Thermo Scientific Revco PLUS Model
Refrigeration System	Up to 20% greater heat removal capacity over ordinary freezers. Ensures faster temperature recovery after door openings.*	Quicker recovery after door openings, ensuring protection of critical samples.	Ultima, Elite, Value
	Consumes up to 15% less power than leading competitor.*	Cost of ownership is lower and is also friendlier to the environment.	
	Emits up to 15% less heat into the environment than leading competitor.*	Less heat is emitted into the lab environment thus requiring less energy and HVAC equipment to keep the lab environment cool.	
	Noise levels are reduced by up to 40% over previous generations, decreasing interruption in the lab.	A quieter freezer allows the unit to be placed directly inside the lab, saving time.	
Microprocessor Control	Set point controls for the temperature and alarm system. NEW feature for the Thermo Scientific Revco Value PLUS!	More precise settings and flexibility for temperature set points and alarm controls.	
PLUS Time Delay	Programmable feature delays restart of a bank of freezers after building power failure allows stabilized power and a uniform re-start.	<ul style="list-style-type: none"> Eliminates costs and down time associated with tripping a circuit breaker after a power failure. Reduces stress on the compressor and electrical components. 	
On Board Diagnostics	The system will report error codes, pointing the researcher or service technician to a probable cause.	Error indications will allow the researcher or service technician to diagnose problems faster, leading to lower down time inconvenience to the researcher and minimizing exposure to samples.	
Automatic Voltage Buck/Boost System	Buck will reduce incoming line voltage in the event the voltage is too high. Boost will provide additional voltage to incoming line voltage in the event voltage is too low.	This feature will add to the longevity of the freezer by stabilizing the voltage to the unit.	
Optional Integrated Back Up System	Integrated back up system is programmable at the user interface.	Provides user with assurance that samples will not be compromised in the event of a power outage.	
Recessed Power Switch	Power switch is recessed into the housing to keep the unit from inadvertently switching off.	Controls down time due to accidentally switching off the power supply.	
Reinforced Shelves	Stiffeners have been added to all stainless steel shelves for excessive loads and impacts.	Allows storage of high-load and non-standard samples, such as microplate hotels.	
Door Mounted Pressure Equalization Port (PEP)	The door mounted PEP does not take up valuable storage space and does not require maintenance (ice removal).	Periodic ice removal from PEP is not required, allowing the researcher to focus on his/her samples and not waste time maintaining the unit.	
Voltage Indicator (Power Monitor)	Voltage indicator button will provide incoming line voltage when pressed.	Provides fast and accurate information on incoming line voltage.	Ultima, Elite
New Communication Outputs (Option)	4-20mA option for additional communication output devices.	Flexibility in options for connecting to remote alarm systems.	
Battery Readout	Readout is in actual voltage and not percentage of voltage in battery.	Provides user with assurance that alarms and displays will function in the event of a power outage.	

Environmentally Friendly*

15% lower power consumption reduces ownership cost and is environment friendly

15% lower heat rejection into the laboratory environment for a more comfortable work environment

20% more heat removal capacity for quick temperature recovery after door openings

40% quieter so they can reside in the lab; this speeds sample preparation and minimizes sample exposure to ambient air

* Based on internal performance data



Safeguarding Your Precious Samples with Advanced Technology and Exceptional Quality

Thermo Scientific Revco PLUS ultra-low temperature freezers combine the highest reliability and superior performance with cost-effective operation and innovative features.

Our Revco® PLUS freezers feature an advanced technology platform, refrigeration, microprocessor controls and high-quality construction, delivering:

› **Maximum Temperature Recovery**

Up to 20% more heat removal capacity over ordinary freezers, ensuring faster temperature recovery after door openings.*

› **Operational Efficiency**

Up to 15% less power to maintain cabinet temperature compared to other freezers.*

› **Comfortable Lab Environment**

Quiet, comfortable operation allows our ultra-low temperature freezers to reside directly in the lab, creating a more productive and efficient work environment.

› **Environmentally-Friendly**

Up to 15% less heat into the lab environment, minimizing air conditioning costs.*

*Features and Benefits
page 1*

*New 32 cu. ft. HD Freezer
page 5*

*Revco Ultima PLUS
page 7*

*Revco Elite PLUS
page 8*

*Revco Value PLUS
page 9*

*Specifications
page 10*



NEW! Thermo Scientific Revco PLUS HD

Our new Revco PLUS HD freezers feature a highly-efficient, innovative thin wall insulation technology. This allows for expanded interior storage capacity without increasing the exterior cabinet footprint.


All Thermo Scientific Revco PLUS freezers feature programmable, easy-to-use microprocessor controls. Our control systems offer real-time visibility and precise setpoints on temperature, power and other critical measurements to continuously ensure the security of your work.



Thermo Scientific Revco Ultima PLUS

Our Revco Ultima PLUS freezers are suited for laboratories that require sophisticated electronic monitors and alarms for the highest level of sample protection.

Ultima PLUS Control Panel



Thermo Scientific Revco Ultima PLUS HD Ultra-Low Temperature Upright Freezers

Model No.	Capacity Cu Ft (L)	Electrical	Amps/Breaker (Plug)	Interior Dimensions H x W x D inches (mm)	Exterior Dimensions H x W x D inches (mm)	Shipping Weight lbs (kg)
ULT2586-10HD-A	24.8 (702)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 34.5 x 24.3 (1283 x 876 x 616)	77.8 x 43.0 x 36.8 (1975 x 1092 x 935)	825 (358)
ULT2586-10HD-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2586-10HD-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2586-10HD-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT3280-10HD-D	31.4 (889)	208-230V/60 Hz 1Ø	12/15 (P4)	50.5 x 39.1 x 27.3 (1283 x 993 x 693)	77.8 x 48.0 x 36.8 (1975 x 1219 x 935)	930 (478)
ULT3280-10HD-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT3280-10HD-W		230V/50 Hz 1Ø	12/13 (P8)			

Thermo Scientific Revco Ultima PLUS Ultra-Low Temperature Upright Freezers

















Model No.	Capacity Cu Ft (L)	Electrical	Amps/Breaker (Plug)	Interior Dimensions H x W x D inches (mm)	Exterior Dimensions H x W x D inches (mm)	Shipping Weight lbs (kg)
ULT1786-10-A	17.4 (493)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 23.5 x 25 (1283 x 597 x 635)	77.8 x 37.0 x 37.0 (1975 x 940 x 940)	720 (326)
ULT1786-10-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT1786-10-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT1786-10-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT2186-10-A	20.4 (578)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 28.5 x 24.3 (1283 x 724 x 616)	77.8 x 42.0 x 36.3 (1975 x 1066 x 922)	770 (349)
ULT2186-10-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2186-10-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2186-10-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT2586-10-A	24.8 (702)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 34.5 x 24.3 (1283 x 876 x 616)	77.8 x 48.0 x 36.3 (1975 x 1219 x 922)	830 (376)
ULT2586-10-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2586-10-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2586-10-W		230V/50 Hz 1Ø	12/13 (P8)			

Thermo Scientific Revco Elite PLUS Ultra-Low Temperature Upright Freezers

Model No.	Capacity Cu Ft (L)	Electrical	Amps/Breaker (Plug)	Interior Dimensions H x W x D inches (mm)	Exterior Dimensions H x W x D inches (mm)	Shipping Weight lbs (kg)
ULT1786-6-A	17.4 (493)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 23.5 x 25 (1283 x 597 x 635)	77.8 x 37.0 x 37.0 (1975 x 940 x 940)	720 (326)
ULT1786-6-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT1786-6-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT1786-6-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT2186-6-A	20.4 (578)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 28.5 x 24.3 (1283 x 724 x 616)	77.8 x 42.0 x 36.3 (1975 x 1066 x 922)	770 (349)
ULT2186-6-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2186-6-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2186-6-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT2586-6-A	24.8 (702)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 34.5 x 24.3 (1283 x 876 x 616)	77.8 x 48.0 x 36.3 (1975 x 1219 x 922)	830 (376)
ULT2586-6-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2586-6-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2586-6-W		230V/50 Hz 1Ø	12/13 (P8)			

Thermo Scientific Revco Value PLUS Ultra-Low Temperature Upright Freezers

Model No.	Capacity Cu Ft (L)	Electrical	Amps/Breaker (Plug)	Interior Dimensions H x W x D inches (mm)	Exterior Dimensions H x W x D inches (mm)	Shipping Weight lbs (kg)
ULT1786-4-A	17.4 (493)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 23.5 x 25 (1283 x 597 x 635)	77.8 x 37.0 x 37.0 (1975 x 940 x 940)	720 (326)
ULT1786-4-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT1786-4-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT1786-4-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT2186-4-A	20.4 (578)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 28.5 x 24.3 (1283 x 724 x 616)	77.8 x 42.0 x 36.3 (1975 x 1066 x 922)	770 (349)
ULT2186-4-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2186-4-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2186-4-W		230V/50 Hz 1Ø	12/13 (P8)			
ULT2586-4-A	24.8 (702)	115V/60 Hz 1Ø	16/20 (P2)	50.5 x 34.5 x 24.3 (1283 x 876 x 616)	77.8 x 48.0 x 36.3 (1975 x 1219 x 922)	830 (376)
ULT2586-4-D		208-230V/60 Hz 1Ø	12/15 (P4)			
ULT2586-4-V		230V/50 Hz 1Ø	12/16 (P7)			
ULT2586-4-W		230V/50 Hz 1Ø	12/13 (P8)			

Models with this code	have this plug	require this receptacle	NEMA Reference	
			Plug	Receptacle
P1			5-15P	5-15R
P2			5-20P	5-20R
P3			5-30P	5-30R
P4			6-15P	6-15R
P5			6-20P	6-20R
P6			6-30P	6-30R
P7 European				
P8 British				

WARRANTY INFORMATION

United States and Canada:


Standard Revco PLUS models carry a 2-year warranty on parts and labor and a total 3, 4, or 5 year warranty on compressor parts for the Value PLUS, Elite PLUS, and Ultima PLUS, respectively.

International (Outside of U.S. and Canada):

Standard Revco PLUS models carry a 16-month full warranty for parts and a total 60-month warranty on compressor parts for the Value PLUS, Elite PLUS, and Ultima PLUS.

CERTIFICATION INFORMATION AND LINE CORD INFO

- Meets NEMA, UL61010-1, UL471, CUL, CE, IEC60335-2-89/Climate Class T (Tropical) criteria
- Calibration Certification Available
- Validation Testing Program Available



Freezers supplied with line cord plugs (P) require corresponding receptacles illustrated in the Line Cord Plug Reference. Catalog selection charts list each standard model with voltage, rated amperage, recommended circuit breaker size and NEMA electrical plug information.

For racks and accessories, please see the Thermo Scientific Revco Rack and Accessory Guide



Thermo Scientific Nalgene and Nunc cryogenic storage give you everything you need to safely store precious specimens, organize freezer space and simplify sample retrieval. Nalgene® and Nunc™ combine to provide one-stop shopping for the widest variety and highest quality of externally and internally threaded cryovials, storage boxes, lab top coolers and “Mr. Frosty” controlled rate freezing containers. For further information, visit www.nalgene.com or www.nuncbrand.com

© 2009 Thermo Fisher Scientific Inc. All rights reserved. Suva is a trademark of E.I. du Pont de Nemours and Company. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details

www.thermo.com/revcoplus

North America: USA/Canada +1 866 984 3766 (866-9-THERMO) www.thermo.com
Europe: Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254-375, Netherlands +31 76 571 4440, Nordic/Baltic countries +358 9 329 100, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203
Asia: China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374, India +91 22 6716 2200, Japan +81 45 453 9220, Other Asian countries +852 2885 4613 **Countries not listed:** +49 6184 90 6940 or +33 2 2803 2180

BRCSREVPLUS0409

